

The one
that creates a
new trend



mini **O** II

Featuring a new 10.1" LCD touch screen, the miniO II gives you power, performance and style in one intelligent POS system

miniO II is an all-in-one integrated POS system with minimized size and maximized utility. The innovative design and brand new 10.1" monitor means it can perform extensively in the restaurant retail and hospitality service sectors. We paid great attention to detail when considering the user interface, thus bringing you a fast and easy way to manage your business. With data input capabilities via the mini keyboard, PLU or touch-screen, 3 different customer display units, Dallas key (optional) and a built-in 2" thermal printer, the miniO II gives you what you expect from your POS system. What's more, we've incorporated the Intel® Atom™ fanless processor ensuring quieter and stress-free usage.



- New 10.1" LCD touch screen
- 2" integrated jam-free printer (Auto-cutter)
- Selectable touch screen, PLU or keyboard input
- HDD data storage compatibility
- Newly designed flat desktop style
- Incorporates the Intel® Atom™ processor for top performance
- Choice of color available on request



Integrated printer

- 2" thermal jam-free printer
- 200mm/sec max, Auto-cutter



Customer display

- Real or Pole type (Optional)
- 16 columns x 2 lines



**Magnetic Stripe Reader (MSR)
Smart Card Reader(SCR)**




- Optional keyboard**
- Mini keyboard
 - PLU keyboard : 55key



CF card socket

Specification



miniO II	
CPU	Intel Atom N270 1.6GHz processor
Chipset	Intel 945GSE + ICH7M
Storage	SATA HDD 2.5inch (Default 320GB)
Memory	DDR2 SODIMM x 1 slot 1GB (MAX. 2GB)
VGA	Intel 945GSE GMA950 Engine
Printer	2" thermal printer(24V) 200mm/sec max(Auto cutter)
Display	10.1" LCD Touch Screen 1024 x 768 resolution
Internal I/O	
Parallel	1 Port (reserved for internal printer)
USB	1 x touch screen, 1 x keyboard, 1 x (MSR, I-Button, SCR)
RS-232	COM 4 reserved for CDP COM 3 reserved for 2" mini printer
LVDS	Main display use
Mini PCIe	1 slot support
External I/O	
USB	Side 1, Rear 2
RS-232	COM 1 ~ 2 with + 5 / 12V power output on 9pin
LAN	GbE LAN
Cash drawer	1 x RJ11 , Cash drawer port
Options	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
SCR	IC card reader
Dallas	Dallas I-button reader
Keyboard	Mini standard keyboard or Programmable keyboard : 55 Key
Customer display	Rear or Pole type (16 x 2)
CF CARD	CF card reader
Qualification	CE, FCC, KC
Power	Adaptor 24V, 2.5A
OS Support	Windows 2000/XP/XPE/7, WinCE 6.0 (on SSD), WEPOS, POSReady 2009/7
Dimension (WxHxD)	393 x 200 x 325(mm)

* Product specifications may differ according to region and may be changed without prior notice.

